



Section 1. Product and Company Identification

Product Identifier **B22 - Platinum Finish**
Product Use
Description: Viscous Blue opaque liquid with light solvent odor

Manufacturer or suppliers' details

P & S Sales, Inc
20943 Cabot Blvd.
Hayward CA 94545

Emergency Number: 800-255-3924
Customer Service: 510-732-2628
Business Fax: 510-732-2632

Section 2. Hazards Identification

GHS Classification

Flammable Liquids : Category 3
Acute toxicity (oral) : Category 1
Acute toxicity (Inhalation) : Category 1
Acute toxicity (dermal) : Category 1
Skin Irritation : Category 2
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)
Specific target organ toxicity - repeated exposure : Category 2 (Liver, Kidney, Central NS)
Specific target organ toxicity - repeated exposure (oral) : Category 2
Aspiration Hazard : Category 1

GHS Label Elements

Hazard pictograms



Hazard Word **Danger**

Hazard Statements

Flammable liquid and vapour
Fatal if swallowed
Fatal in contact with skin
Fatal if inhaled



May be fatal if swallowed and enters airways
Causes skin irritation
May cause drowsiness or dizziness
May cause damage to organs through prolonged or repeated exposure

Precautionary Statements

Keep away from heat/sparks/open flames/hot surfaces – No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/light/.../equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Do not get in eyes, on skin, or on clothing
Wash skin thoroughly after handling
Do not eat, drink or smoke when using this product
Use only outdoors or in a well-ventilated area
Wear protective gloves/protective clothing/eye protection/face protection
Wear respiratory protection

IF SWALLOWED:

Immediately call a POISON CENTER or doctor/physician
Rinse mouth

IF ON SKIN (or hair):

Remove/Take off immediately all contaminated clothing
Rinse skin with water/shower

IF INHALED:

Remove victim to fresh air and keep at rest in a position comfortable for breathing
Immediately call a POISON CENTER or doctor/physician
Get Medical advice/attention if you feel unwell
Do NOT induce vomiting

IF SKIN IRRITATION OCCURS:

Get medical advice/attention
Take off contaminated clothing and wash before reuse

IN CASE OF FIRE:

Use dry sand, dry chemical or alcohol resistant foam for extinction.
Store in a well ventilated place
Keep container tightly closed
Store locked up
Dispose of contents/container to an approved waste disposal plant.

3. Composition Information on Ingredients

CAS Number	Wt %	Component Name
64742-47-8	10-15%	Aliphatic Hydrocarbon, Mixture
68551-19-9	2-10%	C12-C14 Isoalkanes



Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

4. First Aid Measures

EYE CONTACT

If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

SKIN

In case of skin contact, remove any contaminated clothing and wash skin with soap and water. Launder or dry-clean clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

INHALATION

If overcome by vapor, remove from exposure and call a physician immediately. If breathing is irregular or has stopped, start resuscitation, administer oxygen, if available.

INGESTION

If ingested, DO NOT induce vomiting; call a physician immediately.

5. Fire Fighting Measures

Flash Point >89°C (192°F) TCC	Upper Flamability Limit	not established
Auto Ignition 471°C (880°F)	Lower Flamability Limit	not established

EXTINGUISHING MEDIA AND FIRE FIGHTING PROCEDURES

Foam, water spray (fog), dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type of product, depending on size or potential size of fire and circumstances related to the situation. Plan fire protection and response strategy through consultation with local fire protection authorities or appropriate specialists.

Use dry chemical, foam or carbon dioxide to extinguish the fire. "Water may be ineffective", but water should be used to keep fire-exposed containers cool. If a leak or spill has ignited, use water spray to disperse the vapors and to protect persons attempting to stop a leak. Water spray may be used to flush spills away from exposures. Minimize breathing of gases, vapor, fumes or decomposition products. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS

Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.



6. Accidental Release Measures

Precautions Required if Material is Released or Spilled:

Evacuate area of all unnecessary personnel. Wear protective equipment and/or garments described in Section C if exposure conditions warrant. Shut off source, if possible and contain spill. Protect from ignition. Keep out of water sources and sewers. Absorb in a dry, inert material (sand, clay, etc). Transfer to disposal drums using non-sparking equipment.

Waste Disposal (Insure Conformity with all Applicable Disposal Regulations):

Incinerate or place in permitted waste management facility.

7. Handling and Storage

Do not swallow, may be aspirated into lungs. Avoid contact with eyes, skin or clothing. Avoid breathing vapors, mist, fume or dust. Wear protective equipment and/or garments described in Section C if exposure conditions warrant. Wash thoroughly after handling. Launder contaminated clothing before reuse. Use with adequate ventilation. Keep away from heat, sparks and flame. Store in well-ventilated area. Store in tightly closed container. Bond and ground during transfer.

8. Exposure Controls and Personal Protection

64742-47-8	Aliphatic Hydrocarbon, Mixture	TWA 500 ppm, 2000 mg/m ³ , OSHA Z-1 TWA 200 mg/m ³ , ACGIH TWA 400 ppm, 1600 mg/m ³ , OSHA P0
68551-19-9	C12-C14 Isoalkanes	TWA 1200 mg/m ³ , Manufacturer

VENTILATION

Use only with ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air. No smoking, or use of flame or other ignition sources.

RESPIRATORY PROTECTION

Not generally required. Use supplied-air respiratory protection in confined or enclosed spaces, if needed.

PROTECTIVE GLOVES

Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

EYE PROTECTION

Use splash goggles or face shield when eye contact may occur.



OTHER PROTECTIVE EQUIPMENT

Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing, which could result in prolonged or repeated skin contact.

WORK PRACTICES / ENGINEERING CONTROLS

To prevent fire or explosion risk from static accumulation and discharge, effectively bond and/or ground product transfer system in accordance with (THE) National Fire Protection Association PUBLICATIONS.

9. Physical and Chemical Properties

Physical State Liquid	Color Blue	Vapor Press .12 mmHg
pH 7.2	Specific Gravity 1.10	Viscosity 1000 cst
Vapor Density (Air=1) >3	Melting Point °F 32	Odor Aliphatic solvent
Water Solubility partially dispersable	VOC Content 2.42 lb/Gal LVP VOC exempt solvents, Section 15	

10. Stability and Reactivity

Stability Stable	Hazardous Polymerization Not Expected to Occur
Conditions to Avoid	Keep away from extreme heat, Strong Acids, Alkalies and Oxidizers such as Chlorine, other Halogens, Hydrogen Peroxide and Oxygen
Hazardous Decomposition Products	No substances are readily identifiable from composition but no degradation data is available.

11. Toxicological Information

NATURE OF HAZARD AND TOXICITY INFORMATION

Prolonged or repeated skin contact with this product tends to remove skin oils, possibly leading to irritation and dermatitis; however, based on human experience and available toxicological data, this product is judged to be neither a "corrosive" nor an "irritant" by OSHA criteria.

12. Ecological Information

Do not discharge this product into public waters or waterways unless authorized by a National Pollution Discharge Elimination System (NPDES) permit issued by the Environmental Protection Agency (EPA).

13. Disposal Considerations

Options for disposal of this product may depend on the conditions under which it was used. To determine the proper method of disposal, refer to RCRA (40 CFR 261), as well as federal EPA and state and local regulations.

Please refer to Sections 5, 6 and 15 for additional information.



14. Transportation Information

Non-bulk packagings (capacity less than or equal to 119 gallons)
Not regulated

Transported by marine vessel:

Bulk packages (capacity greater than 119 Gallons)

UN1993, Flammable Liquid, N.O.S. (Naphtha Solvent), 3, PG III, ERG #128

15. Regulatory Information

SARA 313

As of the preparation date, this product did not contain a chemical or chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

NFPA 704 Hazard Codes - - - - - Signals

Health : 0
Flammability: 1
Reactivity : 0
Special Haz.: -

Note: Changes made in Sections B, E and F.

CARB VOC info: 14.66% VOC as regulated by CARB Consumer Products requirements, LVP Exempt Solvents

ARB VOC Info: 2.1 lb/gal VOC; 243 g/L

16. Other Information

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.



P & S Sales, Inc.

Safety Data Sheet

B22 - Platinum Finish

Page 7

Revision Date: 2/25/2015
