



Section 1. Product and Company Identification

Product Identifier **RP21 - Pacific Blue, VOC Compliant**
Product Use
Description: Thin Clear Blue liquid with floral fragrance

Manufacturer or suppliers' details

P & S Sales, Inc	Emergency Number: 800-255-3924
20943 Cabot Blvd.	Customer Service: 510-732-2628
Hayward CA 94545	Business Fax: 510-732-2632

Section 2. Hazards Identification

GHS Classification

Flammable Liquids : Category 4

Skin Irritation : Category 2

Eye Irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Aspiration Hazard : Category 1

GHS Label Elements

Hazard pictograms



Hazard Word **Danger**

Hazard Statements

Combustible liquid
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye irritation



May cause drowsiness or dizziness

Precautionary Statements

Keep away from heat/sparks/open flames/hot surfaces – No smoking

Avoid breathing dust/fume/gas/mist/vapours/spray

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

IF SWALLOWED:

Immediately call a POISON CENTER or doctor/physician

IF ON SKIN:

Wash with soap and water

IF INHALED:

Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

IF IN EYES:

Rinse cautiously with water for several minutes

Remove contact lenses if present and easy to do. continue rinsing

Do NOT induce vomiting

IN CASE OF FIRE:

Use dry sand, dry chemical or alcohol resistant foam for extinction.

Store in a well ventilated place

Keep container tightly closed

Store locked up

Dispose of contents/container to an approved waste disposal plant.

3. Composition Information on Ingredients

CAS Number	Wt %	Component Name
64742-47-8	50-90%	Distillates (petroleum), hydrotreated light
64742-88-7	50-90%	Solvent Naphtha (petroleum), medium aliphatic

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

4. First Aid Measures

EYE CONTACT

If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.



SKIN

In case of skin contact, remove any contaminated clothing and wash skin with soap and water. Launder or dry-clean clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

INHALATION

If overcome by vapor, remove from exposure and call a physician immediately. If breathing is irregular or has stopped, start resuscitation, administer oxygen, if available.

INGESTION

If ingested, DO NOT induce vomiting; call a physician immediately.

5. Fire Fighting Measures

Flash Point 89°C (192°F) TCC	Upper Flamability Limit	7.0%
Auto Ignition 215.5°C (420°F)	Lower Flamability Limit	0.6 %

EXTINGUISHING MEDIA AND FIRE FIGHTING PROCEDURES

Foam, water spray (fog), dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type of product, depending on size or potential size of fire and circumstances related to the situation. Plan fire protection and response strategy through consultation with local fire protection authorities or appropriate specialists.

Use dry chemical, foam or carbon dioxide to extinguish the fire. "Water may be ineffective", but water should be used to keep fire-exposed containers cool. If a leak or spill has ignited, use water spray to disperse the vapors and to protect persons attempting to stop a leak. Water spray may be used to flush spills away from exposures. Minimize breathing of gases, vapor, fumes or decomposition products. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS

Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.

6. Accidental Release Measures

CLEAN WATER ACT / OIL POLLUTION ACT

This product may be classified as an oil under Section 311 of the Clean Water Act, and under the Oil Pollution Act. Discharges or spills into or leading to surface waters that cause a sheen must be reported to the National Response Center (1-800-424-8802).

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Shut off and eliminate all ignition sources. Keep people away. Recover free product. Add sand, earth or other suitable absorbent to spill area. Minimize breathing vapors. Minimize skin contact. Ventilate confined spaces. Open all windows and doors. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses, or extensive land areas.



Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, combustible vapors from absorbed material.

7. Handling and Storage

HANDLING PRECAUTIONS

This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

Keep product away from ignition sources, such as heat, sparks, pilot lights, static electricity, and open flames.

8. Exposure Controls and Personal Protection

64742-47-8	Distillates (petroleum), hydrotreated light	400 ppm, 1600 mg/m ³ (OSHA PO) TWA 500 ppm, 2000 mg.m ³ (OSHA PEL 8 hour) TWA 200 mg/m ³ (as total hydrocarbon vapor) ACGIH
64742-88-7	Solvent Naphtha (petroleum), medium aliphatic	400 ppm, 1600 mg/m ³ (OSHA PO) TWA 500 ppm, 2000 mg.m ³ (OSHA PEL 8 hour) TWA 200 mg/m ³ (as total hydrocarbon vapor) ACGIH

VENTILATION

Use only with ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air. No smoking, or use of flame or other ignition sources.

RESPIRATORY PROTECTION

Use supplied-air respiratory protection in confined or enclosed spaces, if needed.

PROTECTIVE GLOVES

Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

EYE PROTECTION

Use splash goggles or face shield when eye contact may occur.

OTHER PROTECTIVE EQUIPMENT

Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing, which could result in prolonged or repeated skin contact.



WORK PRACTICES / ENGINEERING CONTROLS

To prevent fire or explosion risk from static accumulation and discharge, effectively bond and/or ground product transfer system in accordance with (THE) National Fire Protection Association PUBLICATIONS.

9. Physical and Chemical Properties

Physical State Liquid	Color Blue	Vapor Press 1 mmHg
pH N/A	Specific Gravity .82	Viscosity Thin
Vapor Density (Air=1) 4.8	Melting Point °F N/A	Odor Floral/Solvent
Water Solubility Negligible	VOC Content 80%, See Section 15 for more details	

10. Stability and Reactivity

Stability Stable	Hazardous Polymerization Not Expected to Occur
Conditions to Avoid	Keep away from extreme heat, Strong Acids, Alkalies and Oxidizers such as Chlorine, other Halogens, Hydrogen Peroxide and Oxygen
Hazardous Decomposition Products	No substances are readily identifiable from composition but no degradation data is available.

11. Toxicological Information

NATURE OF HAZARD AND TOXICITY INFORMATION

Prolonged or repeated skin contact with this product tends to remove skin oils, possibly leading to irritation and dermatitis; however, based on human experience and available toxicological data, this product is judged to be neither a "corrosive" nor an "irritant" by OSHA criteria.

This product is judged to have an acute oral LD50 (rat) greater than 5 g/kg of body weight, and an acute dermal LD50 (rabbit) greater than 3.16 g/kg of body weight.

12. Ecological Information

Do not discharge this product into public waters or waterways unless authorized by a National Pollution Discharge Elimination System (NPDES) permit issued by the Environmental Protection Agency (EPA).

13. Disposal Considerations

Options for disposal of this product may depend on the conditions under which it was used. To determine the proper method of disposal, refer to RCRA (40 CFR 261), as well as federal EPA and state and local regulations.

Please refer to Sections 5, 6 and 15 for additional information.



14. Transportation Information

Domestic Transportation, not by air:

Non-bulk packagings (capacity less than or equal to 119 gallons)

Not regulated

Transported by marine vessel:

Bulk packages (capacity greater than 119 Gallons)

UN1993, Flammable Liquid, N.O.S. (Naphtha Solvent), 3, PG III

Non-bulk packagings (capacity less than or equal to 1.3 gallons)

Limited Quantity exception: 49 CFR 173.150(b)(3) Packaging under 5 Liter or 1.3 Gallons

Not Regulated

15. Regulatory Information

THRESHOLD PLANNING QUANTITY (TPQ), EPA REGULATION 40 CFR 355

(SARA Sections 301-304)

No TPQ for product or any constituent greater than 1% or 0.1% (carcinogen).

TOXIC CHEMICAL RELEASE REPORTING, EPA REGULATION 40 CFR 372 (SARA Section 313)

This product contains approximately 1.8% 1,2,4-trimethyl benzene.

HAZARDOUS CHEMICAL REPORTING, EPA REGULATION 40 CFR 370 (SARA Sections 311-312)

EPA Hazard Classification Codes: Chronic, Fire

TOXIC SUBSTANCES CONTROL ACT (TSCA)

This product does not contain polychlorinated biphenyls (PCB's).

All components of this product are listed on the U.S. TSCA inventory.

CARB VOC info: 0% VOC as regulated by CARB Consumer Products requirements, LVP-VOC exception

ARB VOC Info: 5.028 lb/gal VOC; 602.2 g/L

16. Other Information

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.



P & S Sales, Inc.

Safety Data Sheet

RP21 - Pacific Blue, VOC Compliant

Page 7

Revision Date: 3/3/2015
