



Section 1. Product and Company Identification

Product Identifier **H10 - Solvent X**

Product Use Description: Clear thin liquid with strong petroleum solvent odor

Manufacturer or suppliers' details

P & S Sales, Inc
20943 Cabot Blvd.
Hayward CA 94545

Emergency Number: 800-255-3924
Customer Service: 510-732-2628
Business Fax: 510-732-2632

Section 2. Hazards Identification

GHS Classification

Flammable Liquids : Category 2

Acute toxicity (Inhalation) : Category 4

Acute toxicity (dermal) : Category 4

Skin Irritation : Category 2

Eye Irritation : Category 2B

Carcinogenicity : Category 2

Specific target organ toxicity - repeated exposure : Category 2 (Auditory System)

Aspiration Hazard : Category 1

GHS Label Elements

Hazard pictograms



Hazard Word **Danger**

Hazard Statements

Highly flammable liquid and vapour
May be fatal if swallowed and enters airways
Harmful in contact with skin
Harmful if inhaled
Causes skin irritation
Causes eye irritation



May cause damage to organs through prolonged or repeated exposure

Precautionary Statements

Do not handle until all safety precautions have been read and understood

Keep away from heat/sparks/open flames/hot surfaces – No smoking

Take precautionary measures against static discharge

Wash skin thoroughly after handling

Use only outdoors or in a well-ventilated area

Use personal protective equipment as required

IF SWALLOWED:

Immediately call a POISON CENTER or doctor/physician

IF ON SKIN (or hair):

Remove/Take off immediately all contaminated clothing

Rinse skin with water/shower

IF INHALED:

Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

IF IN EYES:

Rinse cautiously with water for several minutes

Remove contact lenses if present and easy to do. continue rinsing

Do NOT induce vomiting

IN CASE OF FIRE:

Use dry sand, dry chemical or alcohol resistant foam for extinction.

Store in a well ventilated place

Keep cool

Dispose of contents/container to an approved waste disposal plant.

3. Composition Information on Ingredients

CAS Number	Wt %	Component Name
1330-20-7	10-15	Mixed Xylenes
64742-47-8	50-70	Aliphatic Petroleum Distillates
67-64-1	10-15	Acetone
108-32-7	2-8	1,3-Dioxolan-2-one, 4-methyl-

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

4. First Aid Measures

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician immediately.

Ingestion: Aspiration hazard. If swallowed, vomiting may occur spontaneously, but DO NOT INDUCE. If vomiting occurs,



keep head below hips to prevent aspiration into lungs. Never give anything by mouth to an unconscious person. Call a physician immediately.

Skin Contact: Immediately flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Flash Point 29°C (84°F)

Upper Flamability Limit 1.0%

Auto Ignition 464 °C (867°F)

Lower Flamability Limit 7.0%

Explosion: Above flash point, vapor-air mixtures are explosive within flammable limits noted above. Contact with strong oxidizers may cause fire. Sealed containers may rupture when heated. Sensitive to static discharge.

Fire Extinguishing Media: Dry chemical, foam or carbon dioxide. Water spray may be used to keep fire exposed containers cool, dilute spills to nonflammable mixtures, protect personnel attempting to stop leak and disperse vapors.

Special Information: In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. Vapors can flow along surfaces to distant ignition source and flash back.

6. Accidental Release Measures

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

7. Handling and Storage

Protect against physical damage. Store in a cool, dry well-ventilated location, away from any area where the fire hazard may be acute. Outside or detached storage is preferred. Separate from incompatibles. Containers should be bonded and grounded for transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Use non-sparking type tools and equipment, including explosion proof ventilation. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product. Do Not attempt to clean empty containers since residue is difficult to remove. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, sparks, flame, static electricity or other sources of ignition: they may explode and cause injury or death.

8. Exposure Controls and Personal Protection

1330-20-7 Mixed Xylenes

100 ppm ACGIG TWA

150 ppm ACGIH STEL

100 ppm OSHA Z-1 TWA

435 mg/m³ OSHA Z-1 TWA

64742-47-8 Aliphatic Petroleum Distillates

200 mg/m³ ACGIH TLV (Skin)

5 mg/m³ OSHA VPEL TWA

67-64-1 Acetone

1000 ppm OSHA P0 TWA

250 ppm NIOSH REL TWA



108-32-7

1,3-Dioxolan-2-one, 4-methyl-

None Established

Ventilation System: A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details. Use explosion-proof equipment.

Personal Respirators (NIOSH Approved): If the exposure limit is exceeded and engineering controls are not feasible, a half-face organic vapor respirator may be worn for up to ten times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece organic vapor respirator may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-face piece positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in oxygen-deficient atmospheres. Where respirators are required, you must have a written program covering the basic requirements in the OSHA respirator standard. These include training, fit testing, medical approval, cleaning, maintenance, cartridge change schedules, etc. See 29CFR1910.134 for details.

Skin Protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection: Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Physical State liquid	Color clear	Vapor Press .010 mm Hg
pH N/A	Specific Gravity .827	Viscosity thin
Vapor Density (Air=1) 5	Melting Point °F -42	Odor aromatic solvent
Water Solubility <.01	VOC Content	89.2% VOC, See Section 15 for more information

10. Stability and Reactivity

Stability Stable	Hazardous Polymerization Not Expected to Occur
Conditions to Avoid	Do not allow contact with strong oxidizing agents and strong acids. Keep away from heat, flames, ignition sources and incompatibles.
Hazardous Decomposition Products	Involvement in a fire causes formation of carbon monoxide and unidentified organic components.

11. Toxicological Information

Acute toxicity

Acute oral toxicity : Acute toxicity estimate : 3,523 mg/kg Method: Calculation method

Acute inhalation toxicity Acute toxicity estimate : 4631 ppm Exposure time: 4 h Test atmosphere: gas Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 1,100 mg/kg Method: Calculation method

Carcinogenicity - Assessment : Animal testing did not show any carcinogenic effects.



Reproductive toxicity - Animal testing did not show any effects on fertility. No toxicity to reproduction

12. Ecological Information

Environmental Fate: Following data for xylene: When released into the soil, this material may evaporate to a moderate extent. When released into the soil, this material is expected to leach into groundwater. When released into the soil, this material may biodegrade to a moderate extent. When released into water, this material may evaporate to a moderate extent. When released into water, this material may biodegrade to a moderate extent. When released into the air, this material may be moderately degraded by reaction with photochemically produced hydroxyl radicals. When released into the air, this material is expected to have a half-life of less than 1 day. This material is not expected to significantly bioaccumulate. (mixed xylenes: octanol / water partition coefficient 3.1 - 3.2; bioconcentration factor = 1.3, eels)

Environmental Toxicity: For xylene: This material is expected to be slightly toxic to aquatic life. The LC50/96-hour values for fish are between 10 and 100 mg/l.

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2.6 mg/l Exposure time: 96 h

Biodegradability : Xylene Inoculum: activated sludge Result: Readily biodegradable.

13. Disposal Considerations

Dispose of all waste and contaminated equipment in accordance with all applicable federal, state and local health and environmental regulations. Recovery and reuse, rather than disposal, should be the ultimate goal of handling efforts. The materials resulting from clean-up operations may be hazardous wastes and therefore, subject to specific regulations. Use only licensed transporters and permitted facilities for waste disposal.

14. Transportation Information

Combination package, inner package under 1 Liter
Not Considered Hazardous, exception 173.150(b)(2)

Non-bulk packagings (capacity greater than or equal to 1 Liter)
UN1993, Flammable Liquid, N.O.S. (Naphtha Solvent), 3, PG II

Transported by air or marine vessel:
Bulk or non-bulk packagings
UN1993, Flammable Liquid, N.O.S. (Naphtha Solvent), 3, PG II

15. Regulatory Information

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

CARB VOC info: less than 20% VOC as regulated by CARB Consumer Products requirements, 94510 (d)
ARB VOC Info: 6.338 lb/gal VOC; 722.3 g/L

EPA SARA Title III Chemical Listings
Section 302 Extremely Hazardous Substances (40 CFR 355): None.
Section 304 CERCLA Hazardous Substances (40 CFR 302): None.
Section 311/312 Hazard Class (40 CFR 370):

Acute: Yes

Chronic: Yes

Fire: Yes

Pressure: No



Reactive: No

Section 313 Toxic Chemicals (40 CFR 372): Listed for covered facilities.

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

16. Other Information

Label Hazard Warning (for retail packaging): DANGER: Contains Xylene! Harmful or fatal if swallowed! Call Physician Immediately. Vapor Harmful! KEEP OUT OF REACH OF CHILDREN!

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.

Further information

NFPA:



HMIS III:

HEALTH	2*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic



P & S Sales, Inc.

Safety Data Sheet

H10 - Solvent X

Page 7

Revision Date: 3/17/2015
