



Section 1. Product and Company Identification

Product Identifier M20 - Inspiration Fabric Coating
Product Use Description: Clear thin liquid for use as a fabric stain guard with menthol odor

Manufacturer or suppliers' details

P & S Sales, Inc
20943 Cabot Blvd.
Hayward CA 94545

Emergency Number: 800-255-3924
Customer Service: 510-732-2628
Business Fax: 510-732-2632

Section 2. Hazards Identification

GHS Classification

Flammable Liquids : Category 2

GHS Label Elements

Hazard Pictograms



Hazard Word **Danger**

Hazard Statements

H225: **Highly flammable liquid and vapour**

Precautionary Statements

- P210: **Keep away from heat/sparks/open flames/hot surfaces – No smoking**
- P233: **Keep container tightly closed**
- P240: **Ground/bond container and receiving equipment**
- P242: **Use only non-sparking tools**
- P243: **Take precautionary measures against static discharge**
- P261: **Avoid breathing dust/fume/gas/mist/vapours/spray**
- P271: **Use only outdoors or in a well-ventilated area**
- P280: **Wear protective gloves/protective clothing/eye protection/face protection**
- P303: **IF ON SKIN (or hair):**
- P361: **Remove/Take off immediately all contaminated clothing**
- P353: **Rinse skin with water/shower**
- P370: **IN CASE OF FIRE:**
- P378: **Use dry sand, dry chemical or alcohol resistant foam for extinction.**
- P403: **Store in a well ventilated place**
- P233: **Keep container tightly closed**
- P235: **Keep cool**
- P501: **Dispose of contents/container to an approved waste disposal plant.**



3. Composition Information on Ingredients

CAS Number	Wt %	Component Name
540-88-5	4-7%	t-Butyl Acetate
541-02-6	60-70%	Decamethylcyclopenasiloxane

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

4. First Aid Measures

Eye Contact:

If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

Skin Contact:

In case of skin contact, remove any contaminated clothing and wash skin with soap and water. Launder or dry-clean clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

Inhalation:

If overcome by vapor, remove victim to fresh air and call a physician immediately. If breathing is irregular or has stopped, start resuscitation, administer oxygen, if available.

Ingestion:

If ingested, DO NOT induce vomiting; call a physician immediately.

5. Fire Fighting Measures

EXTINGUISHING MEDIA AND FIRE FIGHTING PROCEDURES

Foam, water spray (fog), dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type of product, depending on size or potential size of fire and circumstances related to the situation. Plan fire protection and response strategy through consultation with local fire protection authorities or appropriate specialists.

Use dry chemical, foam or carbon dioxide to extinguish the fire. "Water may be ineffective", but water should be used to keep fire-exposed containers cool. If a leak or spill has ignited, use water spray to disperse the vapors and to protect persons attempting to stop a leak. Water spray may be used to flush spills away from exposures. Minimize breathing of gases, vapor, fumes or decomposition products. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS

Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.

6. Accidental Release Measures

CLEAN WATER ACT / OIL POLLUTION ACT

This product may be classified as an oil under Section 311 of the Clean Water Act, and under the Oil Pollution Act. Discharges or spills into or leading to surface waters that cause a sheen must be reported to the National Response Center (1-800-424-8802).

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Shut off and eliminate all ignition sources. Keep people away. Recover free product. Add sand, earth



or other suitable absorbent to spill area. Minimize breathing vapors. Minimize skin contact. Ventilate confined spaces. Open all windows and doors. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses, or extensive land areas.

Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, combustible vapors from absorbed material.

7. Handling and Storage

HANDLING PRECAUTIONS

This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

Keep product away from ignition sources, such as heat, sparks, pilot lights, static electricity, and open flames.

8. Exposure Controls and Personal Protection

540-88-5	t-Butyl Acetate	200 ppm (OSHA) PEL (8 hr TWA)
		200 ppm (ACGIH) TLV (8 hr TWA)
541-02-6	Decamethylcyclopenasiloxane	N/A

Ventilation:

Use only with ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air. No smoking, or use of flame or other ignition sources.

Respiratory Protection:

If the exposure limit is exceeded and engineering controls are not feasible, wear a supplied air, full-facepiece respirator, airtight hood, or full-facepiece self-contained breathing apparatus. Breathing air quality must meet the requirements of the OSHA respiratory protection standard (29CFR1910.134).

Protective Gloves:

Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

Eye Protection:

Use splash goggles or face shield when eye contact may occur.

Work Practices:

To prevent fire or explosion risk from static accumulation and discharge, effectively bond and/or ground product transfer system in accordance with (THE) National Fire Protection Association PUBLICATIONS.

9. Physical and Chemical Properties

Flash Point 4°C (39°F) TCC	Upper Flamability Limit 1.7 %	
Auto Ignition 224°C (435°F)	Lower Flamability Limit 1.5 %	
Physical State Liquid	Color Clear/colorless	Vapor Press 42 mmHg
pH NA	Specific Gravity .93	Viscosity



Vapor Density (Air=1) > 1.0

Melting Point °F unknown

Odor menthol

Water Solubility very low

VOC Content 18.4%, 0.53 lb/gal
CARB Exempt and LVP Solvents

10. Stability and Reactivity

Stability Stable

Hazardous Polymerization Not Expected to Occur

Conditions to Avoid Keep away from extreme heat, Strong Acids, Alkalies and Oxidizers such as Chlorine, other Halogens, Hydrogen Peroxide and Oxygen

Hazardous Decomposition Products No substances are readily identifiable from composition but no degradation data is available.

11. Toxicological Information

t-Butyl Acetate
LD50 > 4100 mg/kg (oral - male rat)
LD50 > 2000 mg/kg (male and female rabbit)
Not a skin sensitizer or carcinogenic hazard

12. Ecological Information

t-Butyl Acetate
LC50 = 240 mg/l (96 hour, OECD 203, Rainbow Trout) semi static
EC50 = 350 mg/l (48 hour, Daphnia magna, OECD 202)

13. Disposal Considerations

Options for disposal of this product may depend on the conditions under which it was used. To determine the proper method of disposal, refer to RCRA (40 CFR 261), as well as federal EPA and state and local regulations.

Please refer to Sections 5, 6 and 15 for additional information.

14. Transportation Information

Combination package, inner package under 1 Liter
Not Considered Hazardous, exception 173.150(b)(2)

Non-bulk packagings (capacity greater than or equal to 1 Liter)
UN1993, Flammable Liquid, N.O.S. (Butyl Acetates), 3, PG II

Transported by air or marine vessel:
Bulk or non-bulk packagings
UN1993, Flammable Liquid, N.O.S. (Butyl Acetates), 3, PG II

15. Regulatory Information

TSCA - Inventory Status All Items on TSCA Inventory



TSCA 12(B) - ACC#255846 Fluorinated acrylic copolymer (subject to export notification)
SARA 311/312 - Fire
SARA 313 - None
SARA 302 - None
CA Prop 65 - Contains no known hazardous materials above the safe harbor limits

16. Other Information **Revision Date** 3/4/2020

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH American Conference of Government Industrial Hygienists
LD50 Lethal Dose 50%
AICS Australia, Inventory of Chemical Substances
LOAEL Lowest Observed Adverse Effect Level
DSL Canada, Domestic Substances List
NFPA National Fire Protection Agency
NDSL Canada, Non-Domestic Substances List
NIOSH National Institute for Occupational Safety & Health
CNS Central Nervous System
NTP National Toxicology Program
CAS Chemical Abstract Service
NZIoC New Zealand Inventory of Chemicals
EC50 Effective Concentration
NOAEL No Observable Adverse Effect Level
EC50 Effective Concentration 50%
NOEC No Observed Effect Concentration
EGEST EOSCA Generic Exposure Scenario Tool
OSHA Occupational Safety & Health Administration
EOSCA European Oilfield Specialty Chemicals Association
PEL Permissible Exposure Limit
EINECS European Inventory of Existing Chemical Substances
PICCS Philipines Inventory of Commercial Chemical Substances
MAK Germany Maximum Concentration Values
PRNT Presumed Not Toxic
GHS Globally Harmonized System
RCRA Resource Conservation Recovery Act
>= Greater Than or Equal To
STEL Short-term Exposure Limit
IC50 Inhibition Concentration 50%
SARA Superfund Amendments and Reauthorization Act.
IARC International Agency for Research on Cancer
TLV Threshold Limit Value



IECSC Inventory of Existing Chemical Substances in China

TWA Time Weighted Average

ENCS Japan, Inventory of Existing and New Chemical Substances

TSCA Toxic Substance Control Act

KECI Korea, Existing Chemical Inventory

UVCB Unknown or Variable Composition, Complex Reaction Products, and Biological Materials

<= Less Than or Equal TO

WHMIS Workplace Hazardous Materials Information System

LC50 Lethal Concentration 50%



P & S Sales, Inc.

Safety Data Sheet

M20 - Inspiration Fabric Coating

Page 7

Revision Date: 3/4/2020



P & S Sales, Inc.

Safety Data Sheet

M20 - Inspiration Fabric Coating

Page 8

Revision Date: 3/4/2020



P & S Sales, Inc.

Safety Data Sheet

M20 - Inspiration Fabric Coating

Page 9

Revision Date: 3/4/2020



P & S Sales, Inc.

Safety Data Sheet

M20 - Inspiration Fabric Coating

Page 10

Revision Date: 3/4/2020



P & S Sales, Inc.

Safety Data Sheet

M20 - Inspiration Fabric Coating

Page 11

Revision Date: 3/4/2020
